



WIFI-Link Technologies Inc.



WEB:www.wifi-link.com

Service e-mail : sales@wifi-link.com

Dipole Antenna 2.4G 3dBi

WL-DA-3-RSMA



This compact 3 dBi 2.4GHz OMNI directional "rubber-duck" WiFi antenna provides broad coverage. It is ideally suited for IEEE 802.11b and 802.11g wireless LANs,

This flexible antenna features a tilt-and-swivel reverse-polarity SMA connector, allowing them to be used vertically, at a right angle, or any angle in-between. It is a replacement for RF Reverse Polarity SMA connectors Antennas on the access points or radios and routers, such as D-Link®, Linksys® WET11 and others.

Specifications:

| |
|-------------------------------------|
| Electrical Properties |
| Frequency:2400 - 2483MHz |
| Gain: 3dBi |
| Polarization : vertical |
| SWR : ≤ 2:1 |
| Impedance : 50 Ohm |
| Electrical Wave: $\lambda/4$ DIOPLE |
| Mechanical Properties |
| Antenna Cover: TPU |
| Color: BLACK |
| Operation Temperature:-20~+60 °C |
| Storage Temperature:-30~+75 °C |
| Length: 108mm (Including connector) |
| Connector : SMA-type / RP Male |

